



GLOBALDECK

solid wood

GLOBALDECK is a solid wooden outdoor pavement of top quality and high resistance that gives spaces features associated to both nature and tradition.

They can be produced for fixation system at sight (with steel screws) or for hidden fixation system, using plastic or steel connectors.

These decks are suggested to customize living spaces, giving them exquisiteness and perpetuating a legacy of tradition of high value for future generations.

The main types of wood used in the manufacturing of decks are those from Brazil, (ipê, cumaru and massaranduba) and Africa (kambala iroko, dark kambala / zazange) normally 20/22 mm thick by 100/120/140 mm width. Other types and measures are available under request.

Check our physical samples near our commercial agents.



Check our physical samples near our commercial agents



Thermowood Deck

thermo modified wood

Nordic pine wood deck, is subject to heat and water steam thermic treatment (Thermo-D). With this treatment there is an improvement in wood's dimensional stability (Reduction in the balance moisture) and extended durability (by thermic insulation and drying, and removal of resin, avoiding fungus and rotting).


This modification is a process which improves resistance to biodegradation and UV rays, among others, producing a new material that in the final cycle of life of the product does not represent an environmental danger, more than non-treated wood.

Being Thermo-D wood, it is inserted in durability class 2, according to EN113 standard, expected to last for near 25 years.

Available in 26mm (thick) for 118mm (width) with hidden fixation.

It is possible to supply it in other dimensions, under request.

Check our physical samples near our commercial agents.



Check our physical samples near our commercial agents



Impregnated Deck

wood treated in autoclave

National or Nordic pine deck, treated in class 4 of impregnation.

In this type of modified wood, the impregnation with furfural alcohol (in double vacuum chamber, in cylindrical autoclave/ boiler, under pressure) is a method which allows reducing balance humidity and increase the dimensional stability of wood, based on the introduction of chemical compounds which reduce the hygroscope of wood.

Normally is a cheaper process than the other kinds of treatment, with expected 15 years durability.

Available in standard measures: 20mm thick for 100 or 120mm width.





SPAZIO
DECK

Deck WPC composite

Composite Deck is an alternative to traditional wood. It is a composite of wood and thermo-plastic polymer. Spaziodeck is a 50% wood, 50% PVC.

It is commercialized in two types: 28x150mm and 23x150mm and there are five colours available (dark brown, light brown/ rosewood, black and white).

It is innovating and combines the appearance and nobility of wood with resistance and durability of the polymer.

Main Features

Easy Maintenance

Exemption of surface treatments such as: painting, oil, varnish, waterproofing, etc. A regular surface cleaning is all it takes to keep it in good condition.

Long lasting

It doesn't rot, it doesn't split, and it's fungus free. It is resistant to time and aging.

Eco-friendly

It reuses wood waste. It is totally recyclable and reusable. It doesn't contain any toxic additives.

It is economically profitable


It has a competitive price, great durability and low costs of maintenance, becoming an excellent and long-lasting investment.

Easy to apply

It becomes very easy to apply a deck wpc recurring to conventional tools.

Safety and comfort

It doesn't split or chip. It is less slippery. Its touch is smooth and comfortable.



Check our physical samples near our commercial agents



Components accessories

We have several products to apply on decks which complement our offer:

- Levelling feet
- Wood support profiles (batten), treated wood or WPC;
- Plastic fixing clips and/or metal;
- Lift-off clips;
- Edging boards for composite decks
- Screws.



NDGD201307




Outdoor Pavements

GLOBALDECK, thermowood deck,
impregnated deck and composite deck

GLOBALDIS
FOR YOU, TODAY

GRUPO VICAIMA



GLOBALDIS - Distribuição global de materiais, S.A.

Vale de Cambra
Rua da Vicaima
T. +351 256 426 400

Albufeira
Malhada Velha - Ferreiras
T. +351 289 580 640

Vilar do Pinheiro
Via José Régio, 256
T. +351 229 069 040

geral@globaldis.pt
globaldis.pt

Contact Center 808 50 50 30