

SPC 5mm XL Vinyl Flooring

February 2025



Characteristics

Pattern: 702 Cumberland

Product Code: 999133

EIR – Embossed in Register, synchronised wood shaft





Moisture Resistant: Yes

Click System: Click

Warranty Commercial: 10 years

Warranty Residential: 35 years

Technical features

 Dimensions	
Thickness	4mm SPC + 1mm Screen
Wear Layer Thickness	0,50mm
Length	1524mm
Width	223mm
 Technical features	
Density	2.05 g/cm ³ - Norm EN ISO 23996
Resistance to Chemicals	No change
Gloss level	2% - 4% (super matt)
Formaldehyde	< 0.10 g/mm ³ - Norm EN 717-1:2005
Reaction to fire	Bfl-s1 - Norm EN 13501:2010
Slip rate	R10 - Norm DIN 51130:2014
Click Tensile Strength	Max. 430N/50mm - Norm EN 24334
Residual Indentation	≤ 0.5%
Surface Bonding Strength	2.8 N/mm ²
Boiling Test	No delamination
Abrasion	Class 23 / Class 23 - Norm ISO 10140
Sound Mitigation	> 19 dB
Squareness	≤ 0.05mm - Norm ISO 24337
Straightness	≤ 0.05mm - Norm ISO 24337:10140
Bevel	 V4 - Micro bevel on 4 sides
 Quantity	
Planks per box	7 units
Quantity per box	2,380 m ²

Technical features according to the manufacturer. All materials commercialised by GLOBALDIS must be installed by a competent technician who complies with the installation standards of the respective product. The guarantee for GLOBALDIS products is subject to compliance with the installation standards indicated.

GLOBALDIS endeavours to constantly improve its offer and therefore reserves the right to make changes to the product range or technical specifications without prior notice.